

# Assembly Instruction Sheet #S-1015P32-10-129 For Style 1015P32-10-129

**Tools Required:** Flathead screwdriver, Phillips screwdriver, pliers, wire cutters, wire strippers, electrical tape, safety glasses.  
**Light Source:** (10) E12 Candelabra Base Bulbs, 60W Maximum (Not included).  
**Preparation:** Identify and inspect all parts before beginning installation. Check package content list and diagrams below to be sure all parts are present. If any parts are missing or damaged, do not attempt to assemble, install, or operate the fixture. Contact customer service for replacement parts.

## Warnings and Cautions

Turn off electricity at circuit breaker or main fuse box before installation. Consult a licensed electrician if in doubt. These instructions are provided for your safety. It is very important you read them completely before installing the fixture. We strongly recommend that a licensed, professional electrician perform the installation. Disconnect fixture from power source before replacing bulbs. Make sure bulbs are given sufficient time to cool before removal.

Package Contents		
<b>B</b> Middle Rod		
<b>D1</b> 4*4pcs		
<b>D2</b> 6*2pcs		
<b>D3</b> 12*10pcs		
<b>A</b> Fixture Body x1		
<b>D</b> Ceiling Canopy x1		
<b>C</b> Aluminum pipe x10		
STEP 1 - Release Crossbar from Ceiling Canopy.		
STEP 2-Install Middle Rod to Fixture Body		
	<b>Figure 1</b>	
STEP 3 - Attach Mounting bracket to Outlet Box		
	<b>Figure 2</b>	
STEP 4 - Wire Connections		
	<b>Figure 3</b>	
STEP 5 - Install Ceiling Canopy to Ceiling		
	<b>Figure 4</b>	
STEP 6 - Install Bulbs.		
	<b>Figure 5</b>	
	<b>Figure 6</b>	