

Assembly Instruction Sheet #IS-1020P39-70-602

For Style 1020P39-70-602

Tools Required: Flathead screwdriver, Phillips screwdriver, pliers, wire cutters, wire strippers, electrical tape, safety glasses.
Light Source: (70) SUGGESTED LED G9 BULB MAX 7W(Not Include).
Preparation: Identify and inspect all parts before beginning installation. Check package content list and diagrams below to be sure all parts are present. If any parts are missing or damaged, do not attempt to assemble, install, or operate the fixture. Contact customer service for replacement parts.

Warnings and Cautions
 Turn off electricity at circuit breaker or main fuse box before installation. Consult a licensed electrician if in doubt. These instructions are provided for your safety. It's very important you read them completely before installing the fixture. We strongly recommend that a licensed, professional electrician perform the installation.
 Disconnect fixture from power source before replacing bulbs. Make sure bulbs are given sufficient time to cool before removal.

Hardware Contents	STEP 1 - Install Side Rod to Fixture Body.									
<table border="1"> <thead> <tr> <th>PART</th> <th>DESCRIPTION</th> <th>QUANTITY</th> </tr> </thead> <tbody> <tr> <td>BB</td> <td>Wire nut</td> <td>2pcs</td> </tr> <tr> <td>EE</td> <td>Screw</td> <td>2pcs</td> </tr> </tbody> </table>	PART	DESCRIPTION	QUANTITY	BB	Wire nut	2pcs	EE	Screw	2pcs	<p>Package Contents</p> <ul style="list-style-type: none"> [A] Fixture Body x1 [B] Fixture Body x1 [C] Side Rod X3 [D] Side Rod X6 [E] Glass shade x70 [F] Chain x1 [G] Plate x1 [H] Ceiling Canopy x1 <p>STEP 2 - Install Side Rod to Fixture Body.</p> <p>Figure 1</p> <p>Figure 2</p>
PART	DESCRIPTION	QUANTITY								
BB	Wire nut	2pcs								
EE	Screw	2pcs								

STEP 3 - Install the Canopy Chain Loop and Nipple	STEP 5 - Wire Connections
<p>Figure 3</p>	<p>STEP 4 - Install the Fixture Chain and Ceiling Canopy</p> <p>Figure 4</p> <p>STEP 5 - Wire Connections A. Use standard wire connectors (not included) to make all wire connections. Twist connectors until wires are tightly joined together. Wrap each connection with approved electrical tape and carefully stuff all the connected wires into the Outlet Box.</p> <ul style="list-style-type: none"> - Outlet Box - Hex Nut - Lock Washer - Crossbar - Outlet Box Screw - Nipple - Canopy Chain Loop - Ceiling Canopy - Canopy Lock Ring <p>Figure 5</p> <p>White wire from outlet box</p> <p>Black wire from outlet box (or Red)</p> <p>Bare, or Green Ground wire from outlet box</p> <p>White wire from fixture</p> <p>Black wire from fixture</p> <p>Ground wire from fixture</p> <p>Bare, or Green Ground wire from fixture</p> <p>Green Ground Screw on the Crossbar</p>
<p>STEP 6 - Install Glass shade and Bulbs.</p> <p>Figure 6</p>	