

# Assembly Instruction Sheet #IS-5320P10C For Style 5320P10C

**Tools Required:** Flathead screwdriver, Phillips screwdriver, pliers, wire cutters, wire strippers, electrical tape, safety glasses.

**Light source:** (3) ea Base Bulb 40W Maximum (Not include).


**Preparation:** Identify and inspect all parts before beginning installation. Check package content list and diagrams below to be sure all parts are present. If any parts are missing or damaged, do not attempt to assemble, install, or operate the fixture. Contact customer service for replacement parts.

## Warnings and Cautions

Turn off electricity at circuit breaker or main fuse box before installation. Consult a licensed electrician if in doubt. These instructions are provided for your safety. It is very important you read them completely before installing the fixture. We strongly recommend that a licensed, professional electrician perform the installation.

**Disconnect fixture from power source before replacing bulbs. Make sure bulbs are given sufficient time to cool before removal.**

## Package Contents



## Hardware Contents

| PART | DESCRIPTION      | QUANTITY |
|------|------------------|----------|
| B8   | Wife nut         | 2pcs     |
| CC   | Outlet Box Screw | 2pcs     |

E




Stainless steel cover X1





### STEP 1 – Install the main body of the luminaire


### A. Screw A and F up and down with D




**Figure 1**

## STEP 2 – Install glass rod

**Insert the glass rod into the lamp body and fasten it with E**




**Figure 2**



### STEP 3 – Attach Mounting bracket to Outlet Box

**A.** Pass the supply wires through the Mounting bracket (EE). Attach the Mounting bracket (EE) to the Outlet Box with the head of the Green Ground Screw facing you. Secure it with Outlet Box Screws.


**Tighten until snug.**



**Figure 3**

**STEP 4 – Install Rods to Fixture Body**  
A. Thread the power cord to the Middle Rods.


fix the Middle Rods with the fixture body then the same to connect the other pieces of Rods, finally fix the Canopy with the Rods.



**Figure 4**



**STEP5 – Attach Mounting Screws, Lock Washers and Hex Nuts to Mounting bracket.**

**A.** Line up a set of holes on the Mounting bracket (EE) and Holes on the ceiling canopy.  
Thread Mounting Screws (DD) into the holes on the Mounting bracket (EE). Pass Lock Washers and thread Hex Nuts onto the Mounting Screws (DD).  
Hand tighten until snug.



## STEP 6 – Wire Connections

**A. Use standard wire connectors to make all wire connections. Twist connectors until wires are tightly joined together. Wrap each connection with approved electrical tape and carefully stuff all the connected wires into the Outlet Box.**

**Figure 5**

## STEP 7 - Install bulb and Crystal

**A.** Install bulbs into sockets and screw snug into place.  
**B.** Put the Crystal to the Fixture Body,




Figure 7