

**ASSEMBLY & INSTALLATION  
INSTRUCTION FOR #198-1P**

Please read carefully and save these instructions, as you may need them at a later date.

**CAUTION**

Turn off the main power at the circuit breaker before installing the fixture, in order to prevent possible shock.

**GENERAL**

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician. Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustrations on the installation instructions.

**ASSEMBLY AND INSTALLATION**

There are two installation methods, you can choose one based on the actual situation or requirements.

**The first method (see Fig1)**

1. Adjust the CORD(14) to your desired length(if wire cut needed, please ensure the wire stripped off on the wire end is about 1/2" exposed for the wire connections).
2. After the adjustment of the length of the cord, please slide the "8" WIRE CLAMP(10) near to the COVER PLATE(11), then secure the wire with the PLASTIC SCREW(13) till tight.
3. Secure the BACK PLATE (1) to the ceiling with MOUNTING SCREWS (2).
4. Attach the BLACK SUPPLY WIRE (3) to the BLACK FIXTURE LEAD WIRE (4) by using the WIRE CONNECTOR (9). At the same manner, attach the WHITE SUPPLY WIRE (5) to the WHITE FIXTURE LEAD WIRE (6) and the SUPPLY GROUND WIRE (7) to the FIXTURE GROUND WIRE (8) using the WIRE CONNECTOR (9). Carefully truck the wires and connections inside the COVER PLATE (11).
5. Place the COVER PLATE (11) onto the BACK PLATE(1), and secure with the FIXTURE MOUNTING SCREWS (12) till tight.

**The second method (see Fig2)**

1. Screw the end of the NIPPLE (20) into the center hole of the MOUNTING BRACKET (2) and thread 1/8" IPS HEX NUT(16) onto the end of the NIPPLE(20) but do not tighten the 1/8" IPS HEX NUTS (16).
2. Pass the CORD (14) through the COUPLING(22), the CANOPY(21) and the NIPPLE(20), then, adjust the CORD(14) to your desired length(if wire cut needed, please ensure wire stripped off on the wire end about 1/2" exposed for the wire connections) After the adjustment of the length of the cord, please slide the "8" WIRE CLAMP(10) on the wire near to the NIPPLE (20).
3. Pull the SUPPLY WIRES (3 & 5) and the SUPPLY GROUND WIRE (7) out from the OUTLET BOX (15). Attach the MOUNTING BRACKET (17) assembly to the OUTLET BOX (15) using the MOUNTING SCREWS (18) provided. Rise up the CANOPY (21) through the NIPPLE (20) over the OUTLET BOX (15), and adjust the NIPPLE (20) until the outside threads is around 1/4". Slide down the CANOPY (21), the COUPLING (22) on the CORD and tighten the 1/8" IPS HEX NUTS (16) on the MOUNTING BRACKET (17).

4. Attach the BLACK SUPPLY WIRE (3) to the BLACK FIXTURE LEAD WIRE (4) by using the WIRE CONNECTOR (9). At the same manner, attach the WHITE SUPPLY WIRE (5) to the WHITE FIXTURE LEAD WIRE (6) and the SUPPLY GROUND WIRE (7) to the FIXTURE GROUND WIRE (8) using the WIRE CONNECTOR (9). Place wiring and connections inside the OUTLET BOX (15).
5. Rise up the CANOPY (21) through the NIPPLE (20) over the OUTLET BOX (15), Thread the COUPLING (22) onto the NIPPLE (20) till tight. then secure with the PLASTIC SCREW(13).
6. Screw light bulb into the socket and make sure it does not exceed the maximum wattage specified on the fixture's wattage rating label.

INSTALLATION IS NOW COMPLETED

