

**ASSEMBLY & INSTALLATION  
INSTRUCTION FOR #413-1S-8**

Please read carefully and save these instructions, as you may need them at a later date.

**CAUTION**

Turn off the main power at the circuit breaker before installing the fixture, in order to prevent possible shock.

**GENERAL**

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustrations on the installation instructions.

**ASSEMBLY AND INSTALLATION**

1. Screw the **FIXTURE MOUNTING SCREWS (13)** into the **FIXTURE MOUNTING PLATE (2)** and thread the **HEX NUTS (14)** onto the **FIXTURE MOUNTING SCREWS (13)**, as shown. Secure the position of the **FIXTURE MOUNTING SCREWS (13)** by tightening the **HEX NUTS (14)** against the **FIXTURE MOUNTING PLATE (2)**.
2. Carefully pass the power supply (6&8) wires and the **SUPPLY GROUND WIRE (5)** through the center hole of the **FIXTURE MOUNTING PLATE (2)**. Secure the **FIXTURE MOUNTING PLATE (2)** to the **ELECTRICAL OUTLET BOX (1)** with **MOUNTING PLATE SCREWS (3)**.
3. Thread the **GLASS MOUNTING SCREW(23)** through the hole of the **DECORATIVE FIXTURE RING(25)** and the **GLASS SHADE(26)** into the **HUB FOR ATTACHING GLASS SCREWS(22)** till tight.
4. Thread the **STEM (17) (18) (19)** onto the **THREADED NIPPLE(20)** to get your desired height,. Thread the **SWIVEL ASSEMBLY(16)** into the upper **STEM(17)**.
5. Attach the **BLACK SUPPLY WIRE (8)** to the **SMOOTH (or BLACK) FIXTURE LEAD WIRE (9)** by using the **WIRE CONNECTOR (10)**. At the same manner, attach the **WHITE SUPPLY WIRE (6)** to the **RIBBED (or WHITE) FIXTURE LEAD WIRE (7)**. Loop the **FIXTURE GROUND WIRE (4)** around the **GROUND SCREW (11)** of the **BACK PLATE (2)**. (Note: Be sure to provide an extra 3" length of the **FIXTURE GROUND WIRE (4)** for connection to the **SUPPLY GROUND WIRE (5)**.) Tighten the **GROUND SCREW (11)**. Connect the remaining **FIXTURE GROUND WIRE (4)** to the **SUPPLY GROUND WIRE (5)** using a **WIRE CONNECTOR (10)**. Place wiring and connections inside the **OUTLET BOX (1)**.
6. Place the **DECORATIVE CEILING CANOPY(12)** onto the **FIXTURE MOUNTING SCREWS (13)**, and secure it into place using the **DECORATIVE CAP NUTS(15)** provided.
7. Screw light bulb into the socket and make sure it does not exceed the maximum wattage specified on the fixture's wattage rating label.

INSTALLATION IS NOW COMPLETED

